

BMXP342010

Schneider Electric · Modicon M340

Modicon M340 Performance CPU Module (Level 2, CANopen V1)

Processor

ARM9

Clock speed

180 MHz

Program memory

3584 KB (application + symbols + comments)

Data memory

256 KB (data + constants)

Internal RAM

4096 KB total internal RAM

Programming software

EcoStruxure Machine Expert (Unity Pro)

Scan speed

8.1 Kinst/ms (100% boolean) / 6.4 Kinst/ms (mixed)

Discrete I/O (max)

1024 points

Analog I/O (max)

256 points

Compatible racks

4, 6, 8, 12 slots (X80 racks)

Local racks

1 main rack

Expansion racks

3 expansion racks

Application channels

36

Built-in ports

1× CANopen (RJ45), 1× Modbus Serial (RJ45, RS232/RS485), 1× USB Mini-B

Protocols

CANopen (DS405, master, up to 63 slaves), Modbus Serial (RTU/ASCII)

Communication expansion

Optional X80 communication modules (BMXNOM0200 Modbus serial, BMXNOR0200 CANopen, BMENOC03xx Ethernet/IP, BMXEIA0100 serial)

Supply voltage

24 V DC (via backplane)

Power consumption

2.6 W

Bus current

110 mA @ 24 V DC

Operating temperature

0°C to +60°C

Storage temperature

-25°C to +70°C

www.oilautotech.com

Relative humidity

5% to 95% (non-condensing)

Protection rating

IP20

Dimensions (H×W×D)

100 × 28 × 93 mm

Weight

0.200 kg

Lifecycle

Active/Mature (mid-range platform; newer designs recommended M580) (Last verified: 2026-09)

www.oilautotech.com