

Schneider Service Manual

BMXAMI0410

1. Description

BMXAMI0410

3. Product Information

www.sparetechplc.com

BMXAMI0410

analog input module M340 - 4 inputs - high speed

Main

Range of product Modicon X80

Product or component type Analog input module

Electrical connection 1 connector 20 ways

Input output isolation Isolated

Input level High level

Analogue input number 4

Analogue input type Current +/- 20 mA

Current 0...20 mA

Current 4...20 mA

Voltage +/- 10 V

Voltage +/- 5 V

Voltage 0...10 V

Voltage 0...5 V

Voltage 1...5 V

Complementary

Analog/Digital conversion 24 bits

Analogue input resolution 16 bits

Input impedance 10 MOhm

Permitted overload on inputs +/- 30 V +/- 10 V

+/- 30 V +/- 5 V

+/- 30 V 0...10 V

+/- 30 V 0...5 V

+/- 30 V 1...5 V

+/- 90 mA +/- 20 mA

+/- 90 mA 0...20 mA

+/- 90 mA 4...20 mA

Internal conversion resistor 250 Ohm

Precision of internal conversion

resistor

0.1 % - 15 ppm/°C

Type of filter First order digital filtering

Fast read cycle time 1 ms + 1 ms x number of channels used

Nominal read cycle time 5 ms for 4 channels

Measurement error <= 0.1 % of full scale +/- 10 V 0...60 °C

<= 0.1 % of full scale +/- 5 V 0...60 °C

<= 0.1 % of full scale 0...10 V 0...60 °C

<= 0.1 % of full scale 0...5 V 0...60 °C

<= 0.1 % of full scale 1...5 V 0...60 °C

<= 0.3 % of full scale +/- 20 mA 0...60 °C

<= 0.3 % of full scale 0...20 mA 0...60 °C

<= 0.3 % of full scale 4...20 mA 0...60 °C

0.075 % of full scale +/- 10 V 25 °C

0.075 % of full scale +/- 5 V 25 °C

0.075 % of full scale 0...10 V 25 °C

0.075 % of full scale 0...5 V 25 °C

0.075 % of full scale 1...5 V 25 °C

0.15 % of full scale +/- 20 mA 25 °C

0.15 % of full scale 0...20 mA 25 °C

0.15 % of full scale 4...20 mA 25 °C

Temperature drift 15 ppm/°C +/- 10 V

15 ppm/°C +/- 5 V

15 ppm/°C 0...10 V

15 ppm/°C 0...5 V

15 ppm/°C 1...5 V

30 ppm/°C +/- 20 mA

30 ppm/°C 0...20 mA

www.sparetechplc.com

30 ppm/°C 4...20 mA
Recalibration Internal
Common mode between channels 120 dB
Digital value format +/- 32000 in user scale
+/- 10000 by default
Isolation voltage 300 V DC between channels
1400 V DC between channels and ground
1400 V DC between channels and bus
Measurement resolution 0.35 mV +/- 10 V
0.35 mV +/- 5 V
0.35 mV 0...10 V
0.35 mV 0...5 V
0.35 mV 1...5 V
0.92 µA +/- 20 mA
0.92 µA 0...20 mA
0.92 µA 4...20 mA
Maximum conversion value +/- 11.4 V +/- 10 V
+/- 11.4 V +/- 5 V
+/- 11.4 V 0...10 V
+/- 11.4 V 0...5 V
+/- 11.4 V 1...5 V
0...30 mA +/- 20 mA
0...30 mA 0...20 mA
0...30 mA 4...20 mA
Status LED 1 LED green RUN
1 LED per channel green channel diagnostic
1 LED red ERR
1 LED red I/O
Product weight 0.143 kg
Current consumption 150 mA at 3.3 V DC
45 mA at 24 V DC
Environment
Vibration resistance 3 gn
Shock resistance 30 gn
Ambient air temperature for storage -40...85 °C
Ambient air temperature for operation 0...60 °C
Relative humidity 5...95 % without condensation
IP degree of protection IP20
Product certifications Merchant Navy
RCM
UL
CSA
EAC
CE
Standards EN/IEC 61131-2
CSA C22.2 No 61010-2-201
EN/IEC 61010-2-201
UL 61010-2-201
Protective treatment TC
Operating altitude 0...2000 m
2000...5000 m (with derating factor)
Offer Sustainability
Sustainable offer status Green Premium product
RoHS (date code: YYWW) Compliant - since 0722 - Schneider Electric declaration of conformity

www.sparetechplc.com