

Schneider Series Service Manual

170AEC92000

1. Description

The 170AEC92000 part from Schneider Electric's Modicon series is a versatile module featuring essential functionality for reliable performance. It is certified by UL and CSA standards, ensuring compliance with safety requirements.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Line Modicon
Part	Number 170AEC92000
Weight	1.00 lbs (0.45 kg)
Product	Certifications UL, CSA
Protective	Treatment TC (Tropicalization Protection)
Input	Overvoltage Protection 45V for 10 seconds
Voltage	State 1 (Guaranteed ON) ≥ 11V
Voltage	State 0 (Guaranteed OFF) ≤ 5V
Current	State 1 (Guaranteed ON) ≥ 2.5 mA
Current	State 0 (Guaranteed OFF) ≤ 1.2 mA
Discrete	Output Logic Positive
Discrete	Output Voltage 24V DC
Number	of Counters 2
Discrete	Input Number 6
Discrete	Output Number 4
Range	of Product
Modicon	Momentum automation platform
Product	or Component Type
High	speed counter module base
Group	of channels
2	groups of 3 discrete inputs
2	groups of 2 discrete outputs
Number	of counter
2	
Discrete	input number
6	
Discrete	output number
4	
Complementary	
Discrete	input logic
Positive	
Discrete	input voltage
-	3...30 V DC
24	V DC
Input	overvoltage protection
45	V 10 s
Voltage	state 1 guaranteed
>=	11 V
Voltage	state 0 guaranteed
<=	5 V
Current	state 1 gu

3. Product Information

The 170AEC92000 part from Schneider Electric's Modicon series is a versatile module featuring essential functionality for reliable performance. It is certified by UL and CSA standards, ensuring compliance with safety requirements.

Technical specifications for 170AEC92000

Manufacturer Schneider Electric

Product Line Modicon

Part Number 170AEC92000

Weight 1.00 lbs (0.45 kg)

Product Certifications UL, CSA

Protective Treatment TC (Tropicalization Protection)

Input Overvoltage Protection 45V for 10 seconds

Voltage State 1 (Guaranteed ON) $\geq 11V$

Voltage State 0 (Guaranteed OFF) $\leq 5V$

Current State 1 (Guaranteed ON) $\geq 2.5\text{ mA}$

Current State 0 (Guaranteed OFF) $\leq 1.2\text{ mA}$

Discrete Output Logic Positive

Discrete Output Voltage 24V DC

Number of Counters 2

Discrete Input Number 6

Discrete Output Number 4

Range of Product

Modicon Momentum automation platform

Product or Component Type

High speed counter module base

Group of channels

2 groups of 3 discrete inputs

2 groups of 2 discrete outputs

Number of counter

2

Discrete input number

6

Discrete output number

4

Complementary

Discrete input logic

Positive

Discrete input voltage

- 3...30 V DC

24 V DC

Input overvoltage protection

45 V 10 s

Voltage state 1 guaranteed

$\geq 11\text{ V}$

Voltage state 0 guaranteed

$\leq 5\text{ V}$

Current state 1 guaranteed

$\geq 2.5\text{ mA}$

Current state 0 guaranteed

$\leq 1.2\text{ mA}$

Discrete output logic

Positive

Discrete output voltage

24 V

Discrete output current

1 A per counter

2 A per module

0.5 A per point

Maximum voltage drop

$<0.5\text{ V}$ 0.5 A at state on

Maximum leakage current

www.oilautotech.com

1 mA DC 24 V
Surge current
5 A 1 ms
Response time
< 0.1 ms from state 0 to state 1 output circuit
< 0.1 ms from state 1 to state 0 output circuit
3 ms from state 0 to state 1 input circuit
3 ms from state 1 to state 0 input circuit
Counting input type
Absolute SSI up, down with 4 sub-modes
Incremental up, down, quadrature
Counting input voltage
24 V single ended
5 V differential
Counting frequency
10 kHz single ended
200 kHz differential
Counter inputs resolution
24 bits + sign
Counter configuration
Via comm adapter
Marking
CE
Electrical connection
2 connectors for removable terminal blocks
Current consumption
280 mA 24 V DC
Net Weight
0.46 lb(US) (0.21 kg)
Environment
Resistance to electrostatic discharge
4 kV contact IEC 801-2
8 kV on air IEC 801-2
Resistance to electromagnetic fields
9.1 V/m (10 V/m) 80...1000 MHz IEC 801-3
Product Certifications
UL
CSA
Protective treatment
TC
Ambient Air Temperature for Operation
32...140 °F (0...60 °C)
Ambient Air Temperature for Storage
-40...185 °F (-40...85 °C)
Relative Humidity
95 % without condensation
Operating altitude
<= 16404.2 ft (5000 m)
Ordering and shipping details
Category
US1PC3118206
Discount Schedule
PC31
GTIN
3595861147744
Returnability
No
Country of origin
FR

www.oilautotech.com

Packing Units

Unit Type of Package 1

PCE

Nbr. of units in pkg.

1

Package 1 Height

2.283 in (5.800 cm)

Package 1 Width

7.087 in (18.000 cm)

Package 1 Length

10.315 in (26.200 cm)

Package weight(Lbs)

12.557 oz (356.000 g)

Description

The Schneider Electric Modicon part number 170AEC92000 is engineered for functionality and durability. It features certification from both UL and CSA, indicating adherence to rigorous safety and quality standards. Designed specifically for resilience in tropical environments, the module incorporates TC (Tropicalization Protection) to enhance its operational reliability under challenging conditions.

This module supports multiple input and output connections: with six discrete inputs and four discrete outputs. The discrete outputs operate at 24V DC and incorporate a positive logic structure. Input overvoltage protection is also critical, allowing the device to handle surges of up to 45V for a duration of ten seconds without failure.

Voltage operational states are clearly defined, guaranteeing a voltage state of ON when voltages reach 11V or above and ensuring an OFF state when voltages are 5V or below. Current guarantees further enhance performance, demanding a minimum of 2.5 mA for an ON response while cutting off at 1.2 mA for an OFF state. Furthermore, the presence of two counters grants flexibility for varied applications. Overall, the 170AEC92000 module is designed to ensure precision, stability, and adaptability in industrial automation tasks.

www.oilautotech.com