

Schneider Series Service Manual

170PNT11020

1. Description

The 170PNT11020 from Schneider Electric is a communication adapter designed for Modicon Momentum systems. This adapter employs a Modbus Plus protocol with a baud rate of 1 megabit per second for reliable data transmission.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Type Communication Adapter
Product	Line Modicon Momentum
Part	Number 170PNT11020
EAN	3595861147355
Weight	1.00 lbs (0.45 kg)
Transmission	Cable Type Twisted pairs cable
Communication	Protocol Modbus Plus
Baud	Rate 1 megabits per second
Access	Method Token bus and peer-to-peer (P2P)
Ambient	Operating Temperature 0 to 60°C (in a non-condensing environment)
Number	of Devices Per Segment 0 to 31 per segment and 0 to 64 for all segments
Maximum	Cable Distance Between Devices Approximately 16,404 feet (5,000 meters) with repeater
Protection	Class IP20
Storage	Temperature -40 to 85°C (in a non-condensing environment)
Electrical	Connection Type Two 9-pin D-Sub connectors for redundant and connecting Modbus Plus network
Compliance	Standards UL, CSA, and CE safety standards
Operating	Altitude Less than 16,404 feet (5,000 meters)

3. Product Information

www.oilautotech.com

The 170PNT11020 from Schneider Electric is a communication adapter designed for Modicon Momentum systems. This adapter employs a Modbus Plus protocol with a baud rate of 1 megabit per second for reliable data transmission.

Technical specifications for 170PNT11020

Manufacturer Schneider Electric

Product Type Communication Adapter

Product Line Modicon Momentum

Part Number 170PNT11020

EAN 3595861147355

Weight 1.00 lbs (0.45 kg)

Transmission Cable Type Twisted pairs cable

Communication Protocol Modbus Plus

Baud Rate 1 megabits per second

Access Method Token bus and peer-to-peer (P2P)

Ambient Operating Temperature 0 to 60°C (in a non-condensing environment)

Number of Devices Per Segment 0 to 31 per segment and 0 to 64 for all segments

Maximum Cable Distance Between Devices Approximately 16,404 feet (5,000 meters) with repeater

Protection Class IP20

Storage Temperature -40 to 85°C (in a non-condensing environment)

Electrical Connection Type Two 9-pin D-Sub connectors for redundant and connecting Modbus Plus network

Compliance Standards UL, CSA, and CE safety standards

Operating Altitude Less than 16,404 feet (5,000 meters)

Description

The Schneider Electric 170PNT11020 is a robust communication adapter specifically developed for use within the Modicon Momentum series. It is designed to facilitate data transfer using a twisted pairs cable, ensuring efficient communication.

Operating on the Modbus Plus protocol, this device provides a baud rate of 1 megabit per second, enabling fast data exchange. The access method is based on a token bus and peer-to-peer (P2P) configuration, allowing flexible network topologies for various industrial applications.

This communication adapter can connect up to 31 devices per individual segment and supports a total of 64 devices across all segments, making it versatile for larger setups. The maximum cable length between devices can reach approximately 16,404 feet (5,000 meters) when using a repeater, supporting extensive installations.

The 170PNT11020 operates effectively in ambient temperatures ranging from 0 to 60°C. It also has a wide storage temperature range, functioning in conditions from -40 to 85°C. The unit maintains an IP20 protection class, making it dust-tight, safeguarding against dust and accidental contact.

Electrical connections are facilitated through two 9-pin D-Sub connectors, ensuring redundancy and facilitating integration into the Modbus Plus network. Additionally, this device complies with several safety standards, including UL, CSA, and CE, confirming its reliability in domestic and industrial applications. The recommended operating altitude is below 16,404 feet (5,000 meters). With a weight of just 0.44 pounds (0.2 kilograms), it is lightweight and manageable for installation and use.

Range of Product

Modicon Momentum automation platform

Product or Component Type

Modbus Plus communication adaptor

Bus manager PLC

Premium

Quantum

Structure type

Industrial

Communication Port Protocol

Modbus Plus

Method of access

Token bus

Peer to peer

Transmission Rate

1 Mbit/s

Transmission support medium

Twisted pair

Complementary

Topology

Multidrop, device connecting by extension or tap off cable

Number of devices per segment

0...31 per segment

0...63 all segment

Maximum cable distance between devices

16404.2 ft (5000 m) with repeater

www.oilautotech.com

Data format
IEC 61131-2
Fail state
Full scale value
Forcing to state zero
Maintain value
Fallback to zero
Supply
From I/O base
Marking
CE
Local signalling
1 LED (green) for module powered up or communicating (MB + ACT)
1 LED (red) for communication error network A (ERR A)
1 LED (red) for communication error network B (ERR B)
Electrical connection
1 connector SUB-D 9 for connecting Modbus Plus network
1 connector SUB-D 9 for redundant Modbus Plus network
Environment
Product Certifications
CSA
UL
Standards
FM Class 1 Division 2
Protective treatment
TC
Resistance to electrostatic discharge
4 kV contact IEC 801-2
8 kV on air IEC 801-2
Resistance to electromagnetic fields
9.1 V/m (10 V/m) 80...1000 MHz IEC 801-3
Ambient Air Temperature for Operation
32...140 °F (0...60 °C)
Ambient Air Temperature for Storage
-40...185 °F (-40...85 °C)
Relative Humidity
95 % without condensation
Operating altitude
<= 16404.2 ft (5000 m)
Ordering and shipping details
Category
US1PC3118206
Discount Schedule
PC31
GTIN
3595861147355
Returnability
Yes
Packing Units
Unit Type of Package 1
PCE
Nbr. of units in pkg.
1
Package 1 Height
2.2 in (5.5 cm)
Package 1 Width
7.09 in (18.0 cm)
Package 1 Length
10.2 in (26.0 cm)

www.oilautotech.com

Package weight(Lbs)
7.5 oz (213.0 g)

www.oilautotech.com