

Schneider Series Service Manual

171CCC96030

1. Description

The 171CCC96030 is an M1/M1E Processor Adapter Module from Schneider Electric’s Modicon Momentum series, functioning effectively at a clock frequency of 50 megahertz. It employs Ethernet as its communication protocol, enhancing connectivity options for integration into automation systems.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Type M1/M1E Processor Adapter Module
Product	Line Modicon Momentum
Part	Number 171CCC96030
EAN	3595862000550
Weight	1.00 lbs (0.45 kg)
Clock	Frequency 50 megahertz
Communication	Protocol Ethernet
Memory	Type Flash memory and Random Access Memory (RAM)
Flash	Memory Capacity 1 megabyte
RAM	Capacity 544 kilobytes
Ambient	Operating Temperature 0 to 60°C (in a non-condensing environment)
Rated	Supply Voltage 5 Volts DC
Number	of Communication Ports One Ethernet port and one Input/Output bus port
Register	Input/Output Processor Capacity 26,048 words (maximum)
Scan	Time 0.3 milliseconds per kilobytes
Word	Length 16 bit
Storage	Temperature -40 to 85°C (in a non-condensing environment)
Operating	Altitude Less than 6,561 feet (2,000 meters)
Description	
Schneider	Electric’s 171CCC96030, classified as an M1/M1E Processor Adapter Module, operates at a clock frequency of 50 megahertz. This unit employs Ethernet as its communication protocol, ensuring reliable

3. Product Information

www.oilautotech.com

The 171CCC96030 is an M1/M1E Processor Adapter Module from Schneider Electric’s Modicon Momentum series, functioning effectively at a clock frequency of 50 megahertz. It employs Ethernet as its communication protocol, enhancing connectivity options for integration into automation systems.

Technical specifications for 171CCC96030

Manufacturer Schneider Electric

Product Type M1/M1E Processor Adapter Module

Product Line Modicon Momentum

Part Number 171CCC96030

EAN 3595862000550

Weight 1.00 lbs (0.45 kg)

Clock Frequency 50 megahertz

Communication Protocol Ethernet

Memory Type Flash memory and Random Access Memory (RAM)

Flash Memory Capacity 1 megabyte

RAM Capacity 544 kilobytes

Ambient Operating Temperature 0 to 60°C (in a non-condensing environment)

Rated Supply Voltage 5 Volts DC

Number of Communication Ports One Ethernet port and one Input/Output bus port

Register Input/Output Processor Capacity 26,048 words (maximum)

Scan Time 0.3 milliseconds per kilobytes

Word Length 16 bit

Storage Temperature -40 to 85°C (in a non-condensing environment)

Operating Altitude Less than 6,561 feet (2,000 meters)

Description

Schneider Electric’s 171CCC96030, classified as an M1/M1E Processor Adapter Module, operates at a clock frequency of 50 megahertz. This unit employs Ethernet as its communication protocol, ensuring reliable connectivity in an industrial setting. It comes equipped with 1 megabyte of flash memory alongside 544 kilobytes of RAM, providing adequate storage for operational needs. The capacity for register input/output processing extends to 26,048 words at a 16-bit word length, making it suitable for various applications. The module features a scan time of 0.3 milliseconds per kilobyte, allowing for rapid data processing.

Operating efficiently within an ambient temperature range from 0 to 60°C, this device is intended for use in non-condensing environments. Additionally, its storage temperature range reaches from -40 to 85°C, offering flexibility in installation and use. With a rated supply voltage of 5 volts DC, it is designed for low power consumption.

The 171CCC96030 consists of one Ethernet communication port and one input/output bus port, facilitating effective integration into broader control systems. It is lightweight, at just 0.09 pounds (0.042 kilograms), and is designed to function at operating altitudes of less than 6,561 feet (2,000 meters). This combination of features renders the 171CCC96030 a capable component for advanced automation configurations.

Range of Product

Modicon Momentum automation platform

Product or Component Type

M1/M1E processor adaptor

Concept

Transparent Ready

Level or class

Class B10

Software designation

Concept V2.6

Modsoft >= V2.5

ProWORX NxT V2.0

ProWORX 32

Communication Port Protocol

Ethernet

Processor name

X 86 based (INTEL, AMD) IEC executive

Clock frequency

50 MHz

Complementary

Web services

Rack viewer

Web page loader software tool

Web page loader

Data editor

Ethernet service

www.oilautotech.com

I/O scanning
Modbus TCP messaging
Discrete I/O processor capacity
8192 I/8192 O
Memory Type
1 MB flash
544 kB RAM
Memory description
Program memory 18 kB LL984
Program memory 200 kB IEC
Data 24 kB
Material
Lexan
Word length
16 bit
[Us] rated supply voltage
5.0 V DC +/-5 %
Supply
By Momentum I/O base
Exact time for 1 Kinstruction
1 ms
Register I/O processor capacity
26048 I/26048 O
I/O limit processor capacity
8192 bits max
I/O words/drop
128 I/O Concept
80 I/O ProWORX
Number of port
1 I/O bus
1 ETHERNET
Marking
CE
Net Weight
0.093 lb(US) (0.042 kg)
Environment
Protective treatment
TC
Ambient Air Temperature for Operation
32...140 °F (0...60 °C)
Ambient Air Temperature for Storage
-40...185 °F (-40...85 °C)
Relative Humidity
5...96 % without condensation
Operating altitude
6561.68 ft (2000 m)
Shock resistance
<= 15 gn peak 11 ms half sine wave acceleration
Vibration resistance
1 gn
0.75 mm d.a
Product Certifications
UL
Nema type 250
cUL
FM Class 1 Division 2
Ordering and shipping details
Category
18206-MOMENTUM PROCESSORS,I/O BASES,CONN.

www.oilautotech.com

Discount Schedule
PC31
GTIN
3595862000550
Returnability
No
Country of origin
FR
Packing Units
Unit Type of Package 1
PCE
Nbr. of units in pkg.
1
Package 1 Height
2.4 in (6 cm)
Package 1 Width
7.09 in (18 cm)
Package 1 Length
10.2 in (26 cm)
Package weight(Lbs)
6.9 oz (197 g)

www.oilautotech.com