

Schneider Service Manual

TM3TI4

1. Description

Modicon TM3 - 4 analog /

3. Product Information

www.sparetechplc.com

Modicon TM3 - 4 analog /

temperature inputs (screw) 24Vdc

Main

Range of product Modicon TM3

Product or component type Analog input module

Range compatibility Modicon M221

Modicon M241

Modicon M251

Modicon M262

Analogue input number 4

Analogue input type current 4...20 mA

current 0...20 mA

voltage 0...10 V

voltage - 10...10 V

thermocouple - 200...1000 °C with thermocouple J

thermocouple - 200...1300 °C with thermocouple K

thermocouple 0...1760 °C with thermocouple R

thermocouple 0...1760 °C with thermocouple S

thermocouple 0...1820 °C with thermocouple B

thermocouple - 200...400 °C with thermocouple T

thermocouple - 200...1300 °C with thermocouple N

thermocouple - 200...800 °C with thermocouple E

thermocouple 0...2315 °C with thermocouple C

Ni 100/Ni 1000 temperature probe - 60...180 °C

Pt 100 temperature probe - 200...850 °C

Pt 1000 temperature probe - 200...600 °C

Complementary

Analogue input resolution 16 bits

15 bits + sign

Permissible continuous overload 13 V, analogue input type: voltage

40 mA, analogue input type: current

Input impedance <= 50 Ohm current

>= 1 MOhm voltage

>= 1 MOhm thermocouple

>= 1 MOhm temperature probe

LSB value 2.44 mV 0...10 Vvoltage

4.88 mV - 10...10 Vvoltage

4.88 µA 0...20 mAcurrent

3.91 µA 4...20 mAcurrent

0.1 °Ctemperature probe

0.1 °Cthermocouple

Conversion time 100 ms + 100 ms per channel + 1 controller cycle time for analogue input

thermocouple

100 ms + 100 ms per channel + 1 controller cycle time for analogue input

temperature probe

10 ms + 10 ms per channel + 1 controller cycle time for analogue input voltage/

current

Sampling duration 10 ms, analogue input type: voltage/current

100 ms, analogue input type: voltage/current

100 ms, analogue input type: thermocouple

100 ms, analogue input type: temperature probe

Absolute accuracy error +/- 0.2 % of full scale at 25 °C for analogue input voltage/current

+/- 0.2 % of full scale at 25 °C for Pt 100/Pt 1000, Ni 100/ Ni 1000 temperature probe

+/- 0.2 % of full scale at 25 °C for thermocouple C 0...2315 °C

+/- 6 °C at 25 °C for thermocouple R, S 0...200 °C

+/- 0.2 % of full scale at 25 °C for thermocouple R, S 200...1760 °C

+/- 0.2 % of full scale at 25 °C for thermocouple B 300...1820 °C

+/- 0.4 % of full scale at 25 °C for thermocouple K - 200...0 °C

+/- 0.2 % of full scale at 25 °C for thermocouple K 0...1300 °C

www.sparetechplc.com

+/- 0.4 % of full scale at 25 °C for thermocouple J - 200...0 °C
+/- 0.2 % of full scale at 25 °C for thermocouple J 0...1000 °C
+/- 0.4 % of full scale at 25 °C for thermocouple E - 200...0 °C
+/- 0.2 % of full scale at 25 °C for thermocouple E 0...800 °C
+/- 0.4 % of full scale at 25 °C for thermocouple T - 200...0 °C
+/- 0.2 % of full scale at 25 °C for thermocouple T 0...400 °C
+/- 0.4 % of full scale at 25 °C for thermocouple N - 200...0 °C
+/- 0.2 % of full scale at 25 °C for thermocouple N 0...1300 °C
Temperature drift +/- 0.01 %FS/°C
Repeat accuracy +/-0.5 %FS
Non-linearity +/- 0.2 %FS
Cross talk <= 1 LSB
[Us] rated supply voltage 24 V DC
Supply voltage limits 20.4...28.8 V
Type of cable Twisted shielded pairs cable <30 m for input circuit
Current consumption 45 mA at 5 V DC via bus connector
50 mA at 5 V DC via bus connector
35 mA at 24 V DC via external supply
40 mA at 24 V DC via external supply
Local signalling 1 LED (green) for PWR
Electrical connection 10 x 1.5 mm² removable screw terminal block with pitch 3.81 mm adjustment for inputs and supply
10 x 1.5 mm² removable screw terminal block with pitch 3.81 mm adjustment for inputs
Insulation Between input and supply at 1500 V AC
Between input and internal logic at 500 V AC
Marking CE
Surge withstand 1 kV power supply common mode conforming to IEC 61000-4-5
0.5 kV power supply differential mode conforming to IEC 61000-4-5
1 kV input common mode conforming to IEC 61000-4-5
Mounting support Top hat type TH35-15 rail conforming to IEC 60715
Top hat type TH35-7.5 rail conforming to IEC 60715
plate or panel with fixing kit
Height 90 mm
Depth 70 mm
Width 23.6 mm
Net weight 0.11 kg
Environment
Standards IEC 61131-2
Product certifications CE
UKCA
RCM
EAC
cULus
cULus HazLoc
Resistance to electrostatic discharge
8 kV in air conforming to IEC 61000-4-2
4 kV on contact conforming to IEC 61000-4-2
Resistance to electromagnetic fields
10 V/m 80 MHz...1 GHz conforming to IEC 61000-4-3
3 V/m 1.4 GHz...2 GHz conforming to IEC 61000-4-3
1 V/m 2 GHz...3 GHz conforming to IEC 61000-4-3
Resistance to magnetic fields 30 A/m conforming to IEC 61000-4-8
Resistance to fast transients 1 kV (I/O) conforming to IEC 61000-4-4
Resistance to conducted disturbances
10 V 0.15...80 MHz conforming to IEC 61000-4-6

www.sparetechplc.com

3 V spot frequency (2, 3, 4, 6.2, 8.2, 12.6, 16.5, 18.8, 22, 25 MHz) conforming to
Marine specification (LR, ABS, DNV, GL)
Electromagnetic emission Radiated emissions - test level: 40 dB μ V/m QP class A (10 m) at 30...230 MHz
conforming to IEC 55011
Radiated emissions - test level: 47 dB μ V/m QP class A (10 m) at 230...1000 MHz
conforming to IEC 55011
Immunity to microbreaks 10 ms
Ambient air temperature for
operation
-10...55 °C horizontal installation
-10...35 °C vertical installation
Ambient air temperature for
storage
-25...70 °C
Relative humidity 10...95 %, without condensation (in operation)
10...95 %, without condensation (in storage)
IP degree of protection IP20
pollution degree 2
Operating altitude 0...2000 m
Storage altitude 0...3000 m
Vibration resistance 3.5 mm at 5...8.4 Hz on DIN rail
3 gn at 8.4...150 Hz on DIN rail
Shock resistance 15 gn for 11 ms
Packing Units
Unit Type of Package 1 PCE
Number of Units in Package 1 1
Package 1 Height 7.500 cm
Package 1 Width 10.500 cm
Package 1 Length 12.500 cm
Package 1 Weight 215.000 g

www.sparetechplc.com